

AMENDMENTS TO THE CLAIMS

1-15 (Cancelled)

16. (Currently Amended) A communications network comprising:
an optical transmitter emitting an optical signal at a
first wavelength;

an optical communication path optically coupled to said
optical transmitter, said optical communication path being
configured to carry said optical signal;

a service channel emitter optically coupled to one of said
optical communication path and an alternate optical
communication path, said service channel emitter supplying a
service channel optical signal to said one of said optical
communication path and said alternate optical communication
path, said service channel optical signal being at a second
wavelength different than said first wavelength;

a dispersion compensating ~~fiber~~ module optically coupled to
said optical communication path, said dispersion compensating
module having an associated dispersion characteristic; and

a control circuit operatively coupled to said dispersion
compensation module, said control circuit being configured to
adjust a dispersion characteristic associated with said
dispersion compensating ~~fiber~~ module in response to data carried
by said service channel.

17. (Original) A communications network in accordance with claim 16, wherein said data carried by said service channel include signal quality information associated with said optical signal.

18. (Currently Amended) A communications network in accordance with claim 16, further comprising:

*Al
can*
a plurality of additional optical transmitters optically coupled to said optical communication path, each of said additional optical transmitters emitting a respective one of a plurality of additional optical signals, each of said plurality of additional optical signals being at a respective one of a plurality of wavelengths, each of said plurality of wavelengths being different than said first and said second wavelengths, said dispersion characteristic being adjusted such that said optical signal and each of said plurality of optical signals has substantially the same dispersion.

19. (Original) A communication network in accordance with claim 18, wherein said dispersion is substantially equal to zero.

20. (Original) A communication network in accordance with claim 16, wherein said control circuit includes a thermal regulator coupled to said dispersion compensating fiber, said

thermal regulator being configured to adjust a temperature of said dispersion compensating fiber.

21. (Original) A communication network in accordance with claim 16, wherein said control circuit further comprises:

first circuitry configured to sense said service channel optical signal and generate a sense signal in response thereto, said sense signal carrying said data;

second circuitry coupled to said first circuitry and being configured to output a temperature signal in response to said sense signal; and

Al
conf a thermal regulator coupled to said second circuitry, said thermal regulator compensating a temperature of said dispersion compensating fiber in response to said temperature signal to thereby adjust said dispersion characteristic.

22. (Original) A communication network in accordance with claim 20, wherein said dispersion compensating fiber is substantially encased in a thermally conductive medium.

23. (Currently Amended) A communication network in accordance with claim 16, wherein said dispersion compensating fiber is a first dispersion compensating fiber, said communication network further comprising:

a second dispersion compensating ~~fiber~~ module optically coupled to said optical communication path, said control circuit

being configured to adjust a dispersion characteristic associated with said second dispersion compensating ~~fiber~~ module in accordance with additional data carried by said service channel optical signal.

24. (Cancelled)

25. (New) A communications network in accordance with claim 16,

wherein said dispersion compensating module is a first dispersion compensating module having a first dispersion characteristic,

al
conf wherein said control circuit is a master control circuit, the communications network further comprising:

a second dispersion compensating module optically coupled to the optical communication path, said second dispersion compensating module having a second dispersion characteristic; and

a slave control circuit operatively coupled to said second dispersion compensating module,

said master control circuit generating a master control signal and a slave control signal in response to the data carried by the service channel optical signal,

wherein the first and second dispersion characteristics of the first and second dispersion compensating modules are

respectively adjusted in response to the master and slave control signals.

26. (New) A communications network in accordance with claim 25,

wherein the master and slave control signals substantially equally divide a total amount of dispersion to be compensated between said first and second dispersion compensating modules.

27. (New) A communications network in accordance with claim 25,

*Al
conf* a plurality of said second dispersion compensating modules each having a respective dispersion characteristic, and

a plurality of slave control circuits each of which is associated with a corresponding one of said second dispersion compensating modules.

28. (New) A communications network in accordance with claim 27,

said master control circuit polling each of said slave control circuits to determine the availability of the corresponding second dispersion compensating modules to compensate for dispersion,

said master control circuit generates the master and slave control signals according to the determined availability of each

A' encl. of said second dispersion compensating modules and the data
carried by the service channel optical signal.
